



SEASTAR

Seastar Marine's Catalogue

Brightstar Torches

<https://www.seastar.sg/>

+65 62658662

BRIGHT STAR TORCHES



BRIGHT STAR 2618 Industrial

Specifications :

Power Source : 2xD-cell Alkaline
Bulb/Lamp : PR-2
Life : 15 hrs
Light Output : 10,000 Beam Candlepower

Features:

Distortion free, Vacuum metalized reflector
250,000 Cycle switch
Lens ring accepts accidental lighting
Deep ribbed case for non-slip grip
Proven Industrial quality
Anti-Roll Tube
Crush Resistant reinforced case
Unbreakable Lens



BRIGHT STAR 2618 LED Industrial

Specifications :

Power Source : 2xD-cell Alkaline
Light Source : LED
Life : 30,000 hrs
Runtime : 200hrs
Light Output : 50 Lumens
Beam Distance : 75 Meters

Features:

Distortion free, vacuum metallized reflector
Lens ring accepts snap-in wand
"Switch Guard" prevents accidental lighting
Deep ribbed case for non-slip grip
proven industrial quality
Anti-Roll Tube
Crush-resistant reinforced case
Chemical & Grease Resistant

BRIGHT STAR TORCHES



BRIGHT STAR 2217 SAFETY FLASHLIGHT, 2D CELL

Specifications :

Power Source : 2xD-cell Alkaline
Bulb/Lamp : PR-2
Life : 15 hrs
Light Output : 10,000 Beam Candlepower
Weight (without batteries): 4.5 oz(.13kg)

Features:

Waterproof
Spare bulb compartment
Circuit breaking Mechanism
Tree-way switch : On-Off Flash
Anti-Roll Tube
Oversized, faceted reflector for more light

Safety Approvals

UL Divisions 1 & 2
Class I, Group C & D, Class II, Group G,
Class III
Operating Temp T5
ASTM & MSHA Approved



BRIGHT STAR 2224 SAFETY FLASHLIGHT, 3D CELL

Specifications :

Power Source : 3xD-cell Alkaline
Light Source : PR-3
Life : 15 Hours
Runtime : 200hrs
Light Output : 15,000 Beam Candlepower
Weight (without batteries): 6.0 oz (.17kg)

Features:

For use in hazardous atmospheres
Division 1 UL & CUL approved
Waterproof
Spare bulb compartment
Three-way switch : On-Off Flash
Anti-Roll Tube
Oversize, faceted reflector for more light
Circuit breaking mechanism

Safety Approvals

UL/CUL: Class I, Div 1, Group C & D
Div 2, Group A, B, C, & D
Class II, Div 1, Group G
Operating Temp T3C
CSA: Class I, Div 1, Group C & D
Class II, Div 1, Group G
Operating Temp T3C
ASTM & MSHA: Approved

BRIGHT STAR TORCHES



BRIGHTSTAR 15460 LED FLASHLIGHT, 2D CELL, UL APPROVED (2217-LED)

Specifications :

Power Source : 2xD-cell Alkaline
Bulb/Lamp : LED
Life : 30,000 hrs
Runtime : 200 hrs
Light Output : 40 Lumens/
1,946Candlepower
Beam Distance : 88 Meters
Weight (without batteries): 5.0 oz(.13kg)

Features:

For use in hazardous atmospheres
'S' Biner included for quick attachment
Waterproof, IP67 rating
'Switch Guard' Prevents accidental lighting
Three-way switch : On-Momentary-Off
Anti-Roll Tube
Faceted reflector for more light

Safety Approvals

UL Protection Methods
Intrinsically Safe
Divisions 1 & 2
Class I,II,III Div 1 Groups A-G
Class I,II,III Div 2 Groups A-G
Operating Temp T5



BRIGHTSTAR 15720 LED FLASHLIGHT, 3D CELL, UL APPROVED (2224-LED)

Specifications :

Power Source : 3xD-cell Alkaline
Light Source : PR-3
Life : 15 Hours
Runtime : 200hrs
Light Output : 40 Lumens/ 1,930 Beam
Candlepower
Weight (without batteries): 6.0 oz (.17kg)

Features:

For use in hazardous atmospheres
'S' Biner included for quick attachment
Waterproof, IP67 rating
'Switch Guard' Prevents accidental lighting
Three-way switch : On-Momentary-Off
Anti-Roll Tube
Faceted reflector for more light

Safety Approvals

UL Protection Methods
Intrinsically Safe
Divisions 1 & 2
Class I,II,III Div 1 Groups A-G
Class I,II,III Div 2 Groups A-G
Operating Temp T5

BRIGHT STAR TORCHES



BRIGHTSTAR 2206 SAFETY LANTERN, 6V CELL

Specifications :

Power Source: Alkaline or Carbon Zinc 6V
Lantern Battery
Bulb/Lamp: KPR 113
Bulb/Lamp Life: 15 Hours
Light Output: 50,000 Beam Candlepower
Weight (Without batteries): 14.0 oz

Features:

For use in hazardous atmospheres
Division 1 UL & CUL approved
Waterproof & floating
Krypton Bulb
Alkaline Battery
200 yard light beam projection

Safety Approvals

UL & CUL: Division 1, Class I, Group C & D
When used with one 6V alkaline battery
Division 2 Class I, Group A, B, C, & D
When used with one 6V alkaline battery
Division 1 & 2, Class II, Group G
When used with one 6V carbon zinc
battery
CSA: Division 1 & 2, Class I, Group C & D,
T3
When used with one 6V alkaline battery
Division 1 & 2, Class II, Group G
When used with one 6V carbon zinc
battery
ASTM: Type II
MSHA: Approved for use as mining
equipment

BRIGHT STAR TORCHES



BRIGHTSTAR 08050 LED FLASHLIGHT, 4D/6V CELL, UL APPROVED (2206-LED)

Specifications :

Power Source : 4xD-cell Alkaline
Light Source : LED
Life : 30,000 Hours
Runtime : 150 hrs
Light Output : 90 Lumens

Safety Approvals

UL Protection Methods
Intrinsically Safe
Divisions 1 & 2
Class I,II,III Div 1 Groups A-G
Class I,II,III Div 2 Groups A-G
Operating Temp T5

Features:

For use in hazardous atmospheres
Waterproof, IP67 rating
'D' Cell Alkaline Batteries
'Switch Guard protects switch on impact
Glove friendly handle